



HEAVY COMMERCIAL 910 SERIES

STANDARD FEATURES

- Heavy Commercial rating— meets or exceeds H-HC40 and H-AW40
- 3 ¼" frame depth
- All thermal breaks concealed
- Side load sash with block and tackle balances
- 1" thick insulating glass glazed from interior
- Auto locks at sill
- Full length extruded integral lift handle
- Half screen with aluminum wire standard
- Standard architectural paint finish meets AAMA 2603

OPTIONAL FEATURES

- Unitized frame transom and/or sub-transom available
- Flange frame eliminates need for separate panning
- Sliding screen makes window cleaning easier
- Sash travel limiters
- Optional high performance paint finish (AAMA 2604 or 2605)
- Optional class 1 anodized finish (AAMA 2611)
- Optional class 5 Ultra-Lift balance system
- Oriel (unequal) sash
- Curved frame head

SPECIAL BENEFITS

- Superior structural performance
- Concealed thermal breaks reduce UV damage
- Locks automatically when sash is closed
- Concealed balances reduce vandalism
- Sash removal can be limited to maintenance personnel
- Block and tackle balances provide superior operation
- Sash removes easily for cleaning and maintenance
- Inside glazed— glass can be replaced without disassembling sash
- PVC sash glide and fin-type weatherstrip reduce operating friction

