



HEAVY COMMERCIAL 240 SERIES

STANDARD FEATURES

- AAMA/NWWDA 101/I.S. 2-97 AP-AW60 (Hopper), AP-AW100 (Awning), C-AW65 (Casement)
- Available sash types: hopper, awning and casement
- 2 1/4" frame depth
- 15 PSF water test pressure
- 53 CRF and .5 U-value with Low-e glass
- All frame and sash wall members 0.125" thick
- Flush vent to frame construction
- 1" thick glazing
- Cast white bronze cam locks and keepers
- Concealed 4 bar adj. Friction hinges / 5 knuckle butt hinge on casement

OPTIONAL FEATURES

- Multi-lite and combo units
- Stackable horizontally and vertically
- Pole ring hardware
- Surface applied simulated muntins
- Adaptor to mull with 3 1/4" windows
- Round, arched and gothic frames
- High performance paint finish (AAMA 2604 or 2605)
- Class 1 anodized finish (AAMA 2611)

SPECIAL BENEFITS

- Superior structural performance
- Concealed thermal breaks reduce UV damage
- Flush vent to frame gives a clean appearance
- White bronze hardware gives long term performance
- Custom shaped windows for historical use
- Hydraulically crimped & mitered sash for superior strength
- Flush vent sheds water and eliminates dirt ledges

